

DONA ANA COUNTY BUILDING SERVICES DIVISION

845 N. MOTEL BLVD, RM #150, LAS CRUCES, NM 88007

Phone (575) 647-7350 Fax (575) 525-6131

RESIDENTIAL

REROOF & REROOF/OVERLAY PERMIT REQUIREMENTS

Current Codes: 2015 IRC; 2015 NMRBC; 2009 ENERGY CONSERVATION CODE;
2015 UNIFORM PLUMBING CODE; 2015 NEW MEXICO PLUMBING CODE; 2012 SWIMMING POOL, SPA, HOT TUB CODE; 2015 UNIFORM
MECHINICAL CODE; 2015 NEW MEXICO MECHINICAL CODE; 2012 NEW MEXICO SOLAR ENERGY CODE;
2017 NEC; 2017 NEW MEXICO ELECTRICAL CODE

Incomplete applications are not accepted. 25% of permit fee required at time of application.

1. **Residential:** Invoice or Proposal showing scope of work.
2. **Roofing Material & Manufactures specification.** (See sample attached)
3. **Recorded Proof of Ownership and Legal access with legal description of property (Warranty Deed or Real Estate Contract)** Copy can be obtained at County Clerk's – Room #200

**Homeowner permits require completion of "Instructions for Permit" and "Responsibilities and Liabilities Acknowledgement"
Forms can be found at our website online.*

Warranty Length*

Limited Lifetime* (for as long as you own your home)

Wind Resistance Limited Warranty*

110/130** MPH

Algae Resistance available
in areas shown in white.**Algae Resistance Limited Warranty***

10 Years

TRU PROTECTION® Non-Prorated Limited Warranty® Period

10 Years

Product Specifications

Size	13¼" x 39¾"
Application Exposure	5%*
Shingles per Bundle	Not less than 20
Average Shingle Count per 3 Bundles	64
Average Coverage per 3 Bundles	98.4 sq. ft.

Applicable Standards and Codes

ASTM D228

ASTM D3018 (Type 1)

ASTM D3161 (Class F Wind Resistance)

ASTM D3462

ASTM D7158 (Class H Wind Resistance)

ASTM E108/UL 790 (Class A Fire Resistance)

ICC-ES AC438*

PRI ER 1378E01

Shasta White color meets ENERGY STAR® requirements for initial solar reflectance of 0.25 and 3-year aged solar reflectance of 0.15; 2013 California Building Energy Efficiency Standards, Title 24, Part 6 requirements; rated by the Cool Roof Rating Council (CRRRC).

Total Protection Roofing System^{®A}

TOTAL PROTECTION **SIMPLIFIED**[™]



SEAL.

SELF-ADHERED ICE
& WATER BARRIER
SYNTHETIC UNDERLAYMENT



DEFEND.

STARTER SHINGLES
LAMINATE SHINGLES
HIP & RIDGE SHINGLES



BREATHE.

INTAKE VENTS
EXHAUST VENTS

+ COMFORT.

PINK[®] FIBERGLAS[™]
BLOWN-IN
ATTIC INSULATION

